







Black Solid

White Solid



Stainless Solid

Key Features

- Refrigerator volume of 2.1 cu ft holds up to 24 bottles (12 oz) or Two removable tempered glass shelves 44 cans (12 oz)
- Digital touch pad controls
- Temperature range: 34°F 45°F
- Produces and stores up to 8 lb of ice per day
- Crescent ice cube dimensions: $^{1}/_{2}''$ W x $^{3}/_{4}''$ H x 2 $^{1}/_{4}''$ L
- No drain required

- Field reversible door is shipped right-hand hinged
- Built-in or freestanding

Model Details

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
UARI121-SS01A	115 / 60	Field Reversible	Stainless Solid	101 lb
UARI121-BS01A	115 / 60	Field Reversible	Black Solid	101 lb
UARI121-WS01A	115 / 60	Field Reversible	White Solid	101 lb


Accessories

Model	Description	Finish	Shipping Weight
ULAWATERHOOKUP	Braided water supply line kit	N/A	2 lb

Side Front Top 24" 20 %" (610 mm) 22" (530mm) (559mm) 20 1/3 (521mm) (206mm ICE MAKER AND BIN (213mm) 16 1/4" 21 1/8" (413 mm) 18 1/8 (460mm) 21 ½" 28 1/3" (546mm) (724mm) 17 ½" (445 mm) 4 3/4" (121mm) - 1 1/2" (38mm)

Specifications

Model	ARI121	
Amps: Running	2.5	
Capacity: Bottle (12 oz)	24	
Capacity: Can (12 oz)	44	
Capacity: Refrigerator Volume (cu ft)	2.1	
Defrost Type	Frost Free	
Dimensions: Product Depth	22" / 559 mm	
Dimensions: Product Height	28 ½" / 724 mm	
Dimensions: Product Width	20 %" / 530 mm	
Energy Consumption: Avg. Per Year	565 kWh	
Ice Production Per Day	8 lb	
Ice Storage	8 lb	
Panel Thickness	½" (6.3 mm)	
Product Weight: Max	92 lb	
Refrigerant Type	R600a (1.34 oz)	
Sabbath (Star K Certified)	No	
Temperature Range	34°F - 45°F	




20 1/2

(521mm)

22 1/4

Cabinet Cut-Out



Installation Notes

- When installing a left-hand hinge model, allow for 145° door swing for proper removal of ice bin.
- No additional clearance is needed for ventilation
- Do not obstruct front grille air flow





Warranty

- 1 Year (parts & labor) / 5 year sealed system (parts)
- + Additional 1 Year (parts & labor) warranty at no cost with product registration

See complete warranty for details

(I) UILINE